



Cable eléctrico de cobre multihilos con funda exterior en PVC

Se puede utilizar en el interior, el exterior y en ambiente seco o húmedo.



Ref.	054882	054875	054905	054899	054929	054912	054943	054936	054967	054950	-	056565
Color	●	●	●	●	●	●	●	●	●	●	●	●
Sección (mm ²)	10	16	25	35	50	70						
Grosor de aislamiento	1.4	1.4	1.5	1.7	1.7	1.9						
Ø del cable (mm)	7.3	8.7	10.5	12.0	13.8	15.9						
Hebras	Número	288	204	324	444	636	900					
	Ø (mm)	0.2	0.3	0.3	0.3	0.3	0.3					
Intensidad admisible a 20°C	En funda	50	65	85	106	129	164					
	Suelto	57	73	97	121	145	184					
Resistencia a 20 °C (Ω/km)	1.91	1.31	0.85	0.595	0.419	0.297						
Peso total (kg/km)	130	200	300	410	565	780						
Marcado	HI-FLEX «size» MM ² CE MADE IN EC											
Material de aislamiento	PVC											
Temperatura de funcionamiento	móvil	+5°C / +70°C										
	fijo	-30°C / +70°C										
Tensión nominal U ₀ / U	450 / 750V											
Radio de curvatura	móvil	4 x Ø del cable										
	fijo	3 x Ø del cable										
	100m											
Norma	IEC60332-1 / CEI EN 50265										